



Specification Data Sheet

190 x 15/4 mm. Tongue & Groove (T&G) and Click.

planks are manufactured with a **4mm solid European Oak wear layer** permanently bonded to a **11mm** mixed hardwood plywood substrate. This trusted method of construction provides a long wearing, stable and durable floor with a finished thickness of **15mm**. Ideal for floors, ceilings & walls in residential, multi-residential and commercial construction projects. **Interior use only.**

Key Features; Engineered to exacting standards. Manufactured from sustained yield forest resources. Extremely stable with excellent wear resistance. Wear layer can be re-sanded and rejuvenated throughout the products lifecycle.

Colour Range; in excess of **20 colours**, natural oak, light Scandinavian tones, warm, earthy greys to darker colours. **Raw (un-coated)** available for site specific stain & finishing square edge profile.

Custom colours; Contract colours for multi-residential or commercial projects by arrangement, minimum volume requirements will apply.

Description; Engineered European Oak, **T&G** for direct fix, trowel adhesive installation or **Click** profile for floating installation.

Grade & Surface; **A/B/C/D Grade** contains knots and split defects that are filled and patched to compliment surface colour and character. Pre-finished Matte, German PU coating. Light wire brushed surface.

Size & Length; 190mm width, 15mm thickness, 1900mm length, approx. 30% nested shorter planks, 2 rows / carton, balance set length.

Quantity; 1.805m² / carton, approx. 72 cartons / pallet.

Profile; Tongue & Groove (T&G) or **Click**, Unilin Angle to Angle profile. Micro Bevelled Edges.

Acoustic outcome; Test Result with 2mm Underlay, **L'nT,w 44.**

Fire Test Data; AS/ISO9239.1-2003 (Flooring use) Critical Heat Flux, **4.3kW/m²**. Mean Smoke Development, **8 percent minutes.**

Slip Resistance; In accordance with AS/NZS 4586; 2013 **P3**. **VOC Emissions;** **E1**, (Below World Health Organisation Levels).

R-Value Thermal Resistance; **0.09375**. **JANKA Hardness;** **5.5 – 6.0kN.**

Accessories; Alloy trims, MDF coloured scotia & Stair Nosing available to support colour selection for interior fit-out.

Pre-finished, quick, and easy to lay - no dust, no smell, and no mess.
