

Attributes	Standard	Resistance
Type of floor covering		Unilin Click System
Installation		SPC
Core		5
Colours		650mm x 127mm
Size		9.0mm
Thickness		7.0mm
Core thickness		0.5mm
Wear layer		Embossed
Surface Features		2mm Acoustic underlay
Backing		18 Planks / pack = 1.486m²
Packaging		8.75kg/m² / 17.5kg per pack
Total weight		Micro Bevel Edges
Beveled edge		Commercial: light Domestic:
Classification	ISO 10874 / EN 685 ISO 10874 / EN 685	heavy CHF: ≥10.50kW/m²
Reaction to fire	AS/NZ ISO9239 1-2003	Smoke value: 57%.min
Slip resistance	AS 4586:2013 Appendix A	P3
Dimensional stability	Heat at 60°C for 24 hours	Length: -0.8% Width: -0.09%
Acoustic impact noise reduction	AS/NZ ISO 717.2-2004	FIIC ^{4,5} = 64 L'nTw ³ = 43 AAAC 5 Star Rating ¹
Underfloor heating		Suitable for hydronic underfloor heating, max. 27°C
VOC Emissions	ASTM D5116-17 Green Building Council of Australia Phthalate Free	Compliant for VOC Yes
Quartz content (wt%)		
Warranty	Commercial Domestic	Not detected

10 Years warranty*

25 Years warranty*