

ESTD 2021

AUSTRALISTM COMMERCIAL FLOORING – HOMOGENEOUS VINYL SHEET

Australian made AUSTRALIS is a homogeneous sheet vinyl floor with a contemporary colour palette and bold tone on tone visual, which combines excellent durability and maintenance characteristics. Styled to blend light and shade in a multi chip visual, AUSTRALIS is especially suitable for facilities subject to high daily use.

PRACTICAL

DURABLE

• Broad range of soothing tone on tone neutrals and subtle accents to complement any interior.

• Low maintenance, protective polyurethane reduces initial and ongoing maintenance and increases scuff resistance.

- No need to apply polish.
- Flexible for ease of installation.

TECHNICAL DATA

- Homogeneous construction for excellent dent and gouge resistance.
- Embossed surface texture and multicolour chip visual assist maintenance and help hide soiling and wear patterns.

APPLICATIONS

General traffic areas of:

- Education Office
- Health care Light industrial
- Retail Hospitality

	11	
Type of floor covering	EN ISO 10581	Homogeneous Sheet Vinyl
Manufactured		Australia
Product Identification	EN ISO 10581 .4.1	Type I
Wear Resistance	EN660-2	Group T
Polyurethane Reinforced		Yes PUR
Roll Width	ISO 24341	1.83m
Roll Length	ISO 24341	16m
Overall Thickness	ISO 24362	2.0mm
Coverage		29.28m2
Product Weight	ISO 23997	3.0Kg/m2
Residual Identation	ISO 24343-1	≤ 0.1 mm (PASS)
Flexibility	ISO 24344, Method A	20mm mandrel, no cracking (PASS)
Castor Chair	ISO 4918	25 000 cycles (PASS)
Colour fastness	ISO 105-B02 (Method 3a)	≥ 6 (PASS)
TVOC Emissions	EN 13419-1	<50µg/m2/hr (PASS) (GBCA limit < 500µg/m2/hr))
Slip Resistance	AS4586:2013 (2004) Wet Pendulum Oil Wet *Third party tested, for detail ref	P3(X)* R10* fer to individual Test Reports
Fire Resistance	ISO 9239-1 (Floors) Crital Radiant Flux Smoke Development Rate AS/NZS 3837 (Walls) Cone Calorimeter Average specific extinction area	>7kW/m2 <750% Group 3 < 250m2/kg
Classification (Use Area)	EN ISO 10874 Commerc	Industrial: 43

