

Technical Specifications

EngineeredOakClassicCollection

Attributes	Result
Species	European Oak
Size (L x W x Thickness/top) mm	1900mm x 190mm X 14mm/3mm
Locking system	Tongue & Groove
Pattern	1 Strip Multiply
Core	core 4 sided
Edging	micro bevel
Pack size	2.166m2
Pack weight	22kg 1900mm,
Pack length	6 boards per pack, up to 25% nesting per pack 3mm
Top layer (lamella)	European Oak 8% matte UV lacquer
Surface finish	Floating / Direct stick Swedish Dynea
Installation	
Adhesive	
Fully bonded	
Floated underlay	Yes*
Over under slab heating	No
	Yes*
	Yes*

*Subject to compatible subfloor and correct installation (Refer Installation Instructions)

Test Information & Others	
Origin	Europe
EUTR	Legally harvested timber
FSC	Not available
Janka hardness rating	1360 LBF (7.0)
Slip testing	AS/NZS 4586-2004 Wet: P3
Australian reaction to fire (Floor)	ASISO 9239-1:2003 CRF 4.6kw/m2, smoke value 13%
Environmental rating	A+. Green Building Council of Australia: Pass
Cigarette burns	Repairable
Release of formaldehyde	ASTM D5116 0.093mg/m2/hr (max limit allowable 0.1)
Release of 4-phenylcyclonene	ASTM D5116 <0.004mg/m2/hr (max limit allowable 0.05)
Total VOC	ASTM D5116 0.016mg/m2/hr (max limit allowable 0.5mg/m2/hr)
Warranty (Domestic)	25 Year wear and lifetime structural
Warranty (Commercial)	5 Year wear and lifetime structural