ASTRID

Product Specification Sheet



Description: The Astrid Range is naturally resistant to stains and soiling; Astrid looks and

feels great underfoot. It's palette of eight warm, serviceable colours makes it the

ideal choice for anyone seeking a no-fuss carpet solution.

Type: Solution Dyed Polyester Broadloom Carpet

Construction: Cut pile twist

Pile composition: 100% Solution Polyester

Pile weight: $50 \text{ oz/yd}^2 - 1700 \text{ gm/m}^2 (+/-5\%)$

Finished pile height: 10 mm (+/- 1.0 mm)

Total product thickness: 12 mm (+/- 1.0 mm)

Carpet width: 3.66 metres

Machine gauge: 1/8th

Primary backing: Woven synthetic

Secondary backing: Action Bac

Bond strength: Minimum 30 Newtons

Colours: Elk, Espresso, Jetstream, Maverick, Pitch, Seal, Sienna, Squirrel

Manufacturers Grading: Residential: Heavy Duty, including stairs

Installation: To be installed in accordance with Australian Standard - AS 2455

Stain resistance: Excellent

Static Generation: < 3.5 kV – AS2834

Fire Ratings: Not Fire Rated

VOC: Test Report available on request

Slip Rating: P5 – AWTA (Report 21-002877)

Warranty: 10 Year Residential Wear Warranty

Country of manufacture: Australia

IMPORTANT NOTE: Information contained herein will vary from time to time with the latest information being available at www.questcarpet.com.au In addition, manufacturing processes may necessitate changes to these specifications without prior notice. Important information with relation to Quest Carpets products with relation to installation, care and maintenance, shade and warranties should also be read in conjunction with this document.