

Technical Data Sheet

A690, A691, A692, A693 - 136mm × 1740mm/2190mm × 13.5mm (3.5mm)

Species		Blackbutt* & Spotted Gum*
m2 per Carton		1.4198m2 / 1.787m2
Kg per Carton		Approximately 13.7kg / 17.8kg
Surface		Wire Brush

A694, A695, A696, A697, A698, A699 - 180mm × 1830mm/2190mm × 13.5mm (3.5mm)#

Species		Blackbutt*, Spotted Gum*# & Jarrah#
m2 per Carton		1.9764m2 / 2.3652m2
Kg per Carton		Approximately 18.1kg / 23.2kg
Surface		Wire Brush

Boards per Carton		6 Boards per Carton
Lengths per Carton		Cartons contain set lengths including nested short planks, approx 33%. No more than 2 pieces each nested row
Substrate		Hevea core with bottom layer of birch
Surface Finish		Wire Brush
Coating		Bona Traffic - Matte (10%)
Locking System		Tongue & Groove
Warranty		10 Year Residential Wear 5 Year Light Commercial Wear 25 Year Structural
Edges		Square Edges All 4 Sides
Janka Hardness Rating		9.1 (Blackbutt), 11 (Spotted Gum) & 8.5 (Jarrah)
Dry Slip	AS/NZS 4586-2013	D1
Wet Slip	AS/NZS 4586-2013	P2
VOC Emissions	ASTM D5116:2017 – Total Volatile Organic Compound Emission Rate	0.025mg/m2/hr (max limit allowed <0.5mg/m2/hr)
	STM D5116:2017 – Formaldehyde Emission Rate	0.017mg/m2/hr (max limit allowed <0.1mg/m2/hr)
	ASTM D5116:2017 – 4-phenylcyclohexene Emission Rate	<0.005mg/m2/hr (max limit allowed <0.05mg/m2/hr)
Fire Test	AS/ISO 9239-1:2003	3.2 kW/m2 (Critical Heat Flux / Critical Radiant Flux)
	AS/ISO 9239-1:2003	5.2 kW/m2 (HF-30 Value)
Installation Type		Floating floor, full glue and secret nail
Underfloor Heating		No
Maintenance		As per Definitive native Flooring – Floating Floor Installation and Maintenance Guidelines
Phthalate Free		Yes

*Rustic grade. #Standard & Better grade.