

Technical Data Sheet

228mm × 1524mm × 8.5mm (7mm + 1.5mm IXPE)

Colours		H4170, H4171, H4172, H4173, H4174, H4175, H4176
Thickness		8.5mm (incl 1.5mm IXPE)
m ² per Carton		1.39m ²
Kg per Carton		Approximately 20.5kg
Wear Layer		0.55mm
Surface		EIR (registered emboss) texture feels as grain looks

180mm × 1524mm × 8.5mm (7mm + 1.5mm IXPE)

Colours		H4177, H4178, H4179
Thickness		8.5mm (incl 1.5mm IXPE)
m ² per Carton		1.1m ²
Kg per Carton		Approximately 16.5kg
Wear Layer		0.55mm
Surface		Natural Embossed

Boards per Carton		6 Boards per Carton
Surface Finish		Water Based UV Ceramic Ultra Matt Coating
Locking System		Valinge 5G Patented Click
Warranty		30 year residential 10 year light commercial
Edges		Micro-bevel on all 4 sides
Dry Slip	AS/NZS 4586-2013	D0
Wet Slip	AS/NZS 4586-2013	P4
VOC Emissions	ASTM D5116:2017 – Total Volatile Organic Compound Emission Rate	0.012mg/m ² /hr (max limit allowed <0.500mg/m ² /hr)
	ASTM D5116:2017 – Formaldehyde Emission Rate	0.041mg/m ² /hr (max limit allowed <0.100mg/m ² /hr)
Fire Test	AS/ISO 9239-1:2003	10.9 kW/m ² (Critical Heat Flux / Critical Radiant Flux)
Installation Type		Floating Floor Only
Underfloor Heating		Up to 24°C (surface temperature of subfloor not desired temperature of the room)
Adhesive		None required – floating floor
Environmental Rating		Gold - Greenguard
Phthalate Free		Yes

