

Specification Data Sheet

Oak Parquetry Collection, Herringbone - 120 x 600 x 15/4 mm.

The stunning De Marque Herringbone Parquetry Collection is available with a universal Tongue & Groove profile that assists with pattern alignment and ease of installation. With a contemporary palette of pre-finished colours, the range will provide wonderful warmth and charm to almost any interior.

The parquetry planks are manufactured with a **4mm** solid European Oak wear layer permanently bonded onto a **15mm** mixed hardwood plywood substrate. This trusted method of construction provides a long wearing, stable and durable floor with a finished thickness of **15mm**. Perfectly suited for residential, multi-residential and commercial applications. **Interior use only.**

Key Features; Engineered to exacting standards. Manufactured from sustained yield forest resources. Extremely stable with excellent wear resistance. Wear layer can be re-sanded and rejuvenated throughout the products lifecycle.

Colour Range; Natural oak, light Scandinavian tones, along with warm traditional parquetry colours. **Raw (un-coated)** available for site specific stain & finishing.

Custom colours; Contract colours for multi-residential or commercial projects by arrangement, minimum volume requirements will apply.

Description; Engineered European Oak, Tongue & Groove (T&G) **for direct trowel adhesive installation only.**

Grade & Surface; A/B/C Grade, may contain small knots and natural characteristics that are filled and patched to compliment surface colour and feature. Pre-finished Matte, German PU coating. Light wire brushed surface.

Size & Length; 120mm width, 15mm thickness, 4mm wear layer, 600mm length. **Quantity;** 0.720m² / carton, approx. 88 cartons / pallet.

Profile; Tongue & Groove (T&G), Micro Bevelled Edges.

Acoustic outcome; Test Result, L_{nT,w} 44 (indicative), elastomeric adhesive will contribute to acoustic value.

Fire Test Data; AS/ISO9239.1-2003 (Flooring use) Critical Heat Flux, 4.3kW/m². Mean Smoke Development, 8 percent minutes.

Slip Resistance; In accordance with AS/NZS 4586; 2013 **P3**. **VOC Emissions;** E1, (Below World Health Organisation Levels).

R-Value Thermal Resistance; 0.09375. **JANKA Hardness;** 5.5 – 6.0kN.

Accessories; Alloy trims, MDF coloured scotia & Stair Nosing available to support colour selection for interior fit-out.

Pre-finished, quick, and easy to lay - no dust, no smell, and no mess. Please consult with your supplier for specific site install guidelines prior to installation. For specification or reseller support contact, [or a local sales office.](#)