

EUREKA TOWER

Product Specification Sheet



Description:	Oozing style with its textured loop pile design, Eureka Tower is sensationally stain resistant and available in a collection of designer colours.
Type:	Solution Dyed Nylon Carpet
Construction:	Multi level loop pile
Pile composition:	100% Solution Dyed Nylon
Pile weight:	32 oz/yd ² - 1088 gm/m ² (+/- 5%)
Finished pile height:	10 mm (+/- 1.0 mm)
Total product thickness:	12 mm (+/- 1.0 mm)
Carpet width:	3.66 metres
Machine gauge:	1/4
Primary backing:	Woven synthetic
Secondary backing:	Action Bac
Bond strength:	Minimum 30 Newtons
Colours:	Apostle, Bungle, Cape, Gold Fields, Kiama, Otways, Pinnacle, Seaside
ACCS Grading:	Residential: Extra Heavy Duty, including stairs – 5 Stars (#22191) Commercial: Medium Duty, including stairs – 2 Stars (#22191)
Installation:	To be installed in accordance with Australian Standard - AS 2455
Pattern Match:	14mm Horizontal x 35mm Vertical
Stain resistance:	Excellent
Static Generation:	< 3.5 kV – AS2834
Fire Ratings:	Not Fire Rated
VOC:	Test available on request
Slip Rating:	CSIRO Certificate of Assessment (Report no EP153410) not less than P3
Warranty:	15 Year Residential Wear Warranty
Country of manufacture:	Australia

IMPORTANT NOTE: Information contained herein will vary from time to time with the latest information being available at www.questcarpet.com.au In addition, manufacturing processes may necessitate changes to these specifications without prior notice. Important information with relation to Quest Carpets products with relation to installation, care and maintenance, shade and warranties should also be read in conjunction with this document.