



Specification Data Sheet

190 x 15/4mm. Tongue & Groove (T&G) and Click.

Planks are manufactured with a **4mm solid European Oak wear layer** permanently bonded to a **11mm** mixed hardwood plywood substrate. This trusted method of construction provides a long wearing, stable and durable floor with a finished thickness of **15mm**. Ideal for floors, ceilings & walls in residential, multi-residential and commercial construction projects. **Interior use only**

Key Features; Engineered to exacting standards. Manufactured from sustained yield forest resources. Extremely stable with excellent wear resistance. Wear layer can be re-sanded and rejuvenated throughout the product's lifecycle.

Description; Engineered European Oak, T&G for direct fix, trowel adhesive installation or **Click** profile for floating installation

Grade & Surface: A/B/C/D **Grade** contains knots and split defects that are filled and patched to compliment surface colour and character.

Pre-finished Matte, German PU coating. Light wire brushed surface.

Size & Length; 190mm width, 15mm thickness, 1900mm length, approx. 20% nested shorter planks, 2 rows / carton, balance set length.

Quantity; 1.805m² / carton.

Profile; Tongue & Groove (T&G) or **Click**, Unilin Angle to Angle profile. Micro Bevelled Edges.

Acoustic outcome; Test Result with 2mm Underlay, L'nT,w 44.

Fire Test Data; AS/ISO9239.1-2003 (Flooring use) Critical Heat Flux, **4.3kW/m²**. Mean Smoke Development, **8 percent minutes**

Slip Resistance; In accordance with AS/NZS 4586; 2013 **P3**. **VOC Emissions;** E1, (Below World Health Organisation Levels).

R-Value Thermal Resistance; **0.09375**. **JANKA Hardness;** 5.5 - 6.0kN.

Accessories; Alloy trims, MDF coloured scotia & Stair Nosing available to support color selection for interior fit-out.

Pre-finished, quick, and easy to lay - no dust, no smell, and no mess.