

Specification Data Sheet

Herringbone Parquetry - 120 x 600 x 15/4mm.

This stunning collection is available with a universal Tongue & Groove profile that assists with pattern alignment and ease of installation. With a contemporary palette of pre-finished colours, the range with provide wonderful warmth and charm to almost any interior.

Planks are manufactured with a 4mm solid European Oak wear layer permanently bonded to a 1lmm mixed hardwood plywood substrate. This trusted method of construction provides a long wearing, stable and durable floor with a finished thickness of 15mm. Ideal for floors, ceilings & walls in residential, multi-residential and commercial construction projects. Interior use only

Key Features; Engineered to exacting standards. Manufactured from sustained yield forest resources. Extremely stable with excellent wear resistance. Wear layer can be re-sanded and rejuvenated throughout the product's lifecycle.

Description; Engineered European Oak, Tongue & Groove (T&G) for direct trowel adhesive installation only.

Grade & Surface: A/B/C Hi. Spec. Grade may contain small knots and natural characteristics that are filled and patched to compliment surface colour and feature. Pre-finished Matte, German PU coating. Light wire brushed surface.

Size & Length; 120mm width, 15mm thickness, 4mm wear layer, 600mm length.

Profile; Tongue & Groove (T&G), Micro Bevelled Edges.

Acoustic outcome; Test Result, L'nT,w 44 (indicative). elastomeric adhesive will contribute to acoustic value.

Fire Test Data; AS/ISO9239.1-2003 (Flooring use) Critical Heat Flux, 4.3kW/m2. Mean Smoke Development, 8 percent minutes

Slip Resistance; In accordance with AS/NZS 4586; 2013 P3. VOC Emissions; E1, (Below World Health Organisation Levels).

R-Value Thermal Resistance; 0.09375. JANKA Hardness; 5.5 - 6.0kN.

Accessories; Alloy trims, MDF coloured scotia & Stair Nosing available to support color selection for interior fitout.

Pre-finished, quick, and easy to lay - no dust, no smell, and no mess.