



ESTD 2021

Specification Data Sheet

Herringbone Parquetry - 120 x 600 x 14/3mm.

Features a **Hi-Spec A/B/C visual grade** wear layer providing a cleaner, sharper look. The product is manufactured with a Tongue & Groove profile that assists with pattern alignment and ease of installation. With a tight palette of pre-finished colours that includes natural oak along with light to darker tones, ready to deliver an eye-catching impact for your next project.

Planks are manufactured with a **3mm solid European Oak wear layer** permanently bonded to a **11mm** mixed hardwood plywood substrate. This trusted method of construction provides a long wearing, stable and durable floor with a finished thickness of **14mm**. Ideal for floors, ceilings & walls in residential, multi-residential and commercial construction projects. **Interior use only**

Key Features; Engineered to exacting standards. Manufactured from sustained yield forest resources. Extremely stable with excellent wear resistance. Wear layer can be re-sanded and rejuvenated throughout the product's lifecycle.

Description; Engineered European Oak, Tongue & Groove profile. **Herringbone Parquetry adhesive fix only.**

Grade & Surface: A/B/C Hi. Spec. Grade may contain small knots, sapwood and natural characteristics that are filled and patched to compliment surface colour and feature. Pre-finished Matte, PU laquer coating. Light wire brushed surface.

Size & Length; 120mm width, 14/3mm thickness, 3mm wear layer, 600mm length.

Profile; Tongue & Groove (T&G), Micro Bevelled Edges.

Acoustic outcome; Plank Test Result on 2mm Underlay, L'nT,w 45. **Parquetry requires direct trowel adhesive install, cannot be floated.**

Fire Test Data; AS/ISO9239.1-2003 (Flooring use) Critical Heat Flux, 3.5kW/m². Mean Smoke Development, 26 percent minutes

Slip Resistance; In accordance with AS/NZS 4586; 2013 P3. **VOC Emissions;** E1, (Below World Health Organisation Levels).

R-Value Thermal Resistance; 0.0875. **JANKA Hardness;** 5.5 - 6.0kN.

Accessories; Alloy trims, MDF coloured scotia & Stair Nosing available to support color selection for interior fit-out.

Pre-finished, quick, and easy to lay - no dust, no smell, and no mess.