



ESTD 2021

TECHNICAL SPECIFICATIONS

Specification

Wear Layer
Timber Grade: ABCD
Natural timber colour variation
Thickness: 2mm
Finish: Various
UV Coating 8 layer

Structure

8 Layer multi-ply
Eucalyptus core
(European Oak)

Joins

Lock System: Droplock
Join Treatment: Waxed
Edge Treatment: Micro Bevel

1900 x 190 x 14 2mm

6 Boards
2.12sqm
30% Short
planks 22kg

Warranty

Residential 20 Year Wear
Lifetime Structural
Commercial 5 Year Wear
Lifetime Structural

Test Data

Emission Test ASTM
D5116-2017
- VOC Pass
- Formaldehyde Emission Pass

Herringbone

600 x 120 x 14/2mm

14 Left Side Boards
14 Right Side Boards
2.016sqm
20.5kg

Reaction to fire tests

- CHF Value	3.1 KW/m ² Mean
- HF-30 Value	3.4 KW/m ² Mean
- Smoke Value	16 %min Mean
Blistering	Yes
Penetration of flame through to substrate	Yes

Acoustic Test

Tested to:
AS ISO 140.6-2006 and ISO 10140
Part 3 (2010)
AS ISO 717.2 (2004) Part 2
Certification available on request.

Slip Resistance Classification

Wet Pendulum	P2
--------------	----