

Technical Data

Attributes	Standard	Result
Type of floor covering		H4040 ~ H4049
Installation		5G® Click
Core		SPC
Colours		10
Size		1420 x 225 mm
Thickness		8.5 mm
Core thickness		6 mm
Wear layer		0.5 mm
Surface treatment		PU coating
Backing		2.0 mm EVA underlay
Packaging		6 planks / pack = 1.917 m ²
Total weight		12.57 kg/m ² / 24.10 kg per pack
Beveled edge		4 sided micro bevel
Classification	ISO 10874 / EN 685 ISO 10874 / EN 685	Commercial: light Domestic: heavy
Reaction to fire	AS/NZ ISO9239 1-2003	CHF: 9.3 kW/m ² Smoke Value: 207% -min
Slip resistance	AS 4586-2013 Amdt 1-2017 Appendix A	SRV 37 / P3
Dimensional stability	Heat at 60 °C for 24 hours	Length: -0.15% Width: -0.15%
Acoustic impact noise reduction	AS/NZ ISO 717.2-2004	FIIC5,6 = 62 L'nTw3 = 42 AAAC 5 Star Rating
Underfloor heating		Suitable for hydronic underfloor heating, max. 27°C
Environmental	ASTM D5116-17 Green Building Council of Australia Phthalate Free	Compliant for VOC Yes
Quartz content (wt%)		Not detected
Warranty*	Commercial Domestic	10 years wear* 25 years wear*

